

# Rotating electrical machines —

## Part 17: Cage induction motors when fed from converters — Application guide

ICS 29.160

## National foreword

This Draft for Development reproduces verbatim IEC/TS 60034-17:2006. It supersedes DD IEC/TS 60034-17:2002 which is withdrawn.

### **This publication is not to be regarded as a British Standard.**

It is being issued in the Draft for Development series of publications and is of a provisional nature. It should be applied on this provisional basis, so that information and experience of its practical application can be obtained.

A review of this Draft for Development will be carried out not later than 2 years after its publication.

Notification of the start of the review period, with a request for the submission of comments from users of this Draft for Development, will be made in an announcement in the appropriate issue of *Update Standards*. According to the replies received, the responsible BSI Committee will judge whether the Draft for Development can be converted into a British Standard or what other action should be taken.

Observations which it is felt should receive attention before the official call for comments will be welcomed. These should be sent to the Secretary of BSI Technical Committee PEL/2, Rotating electrical machines, at British Standards House, 389 Chiswick High Road, London W4 4AL, giving the document reference and clause number and proposing, where possible, an appropriate revision of the text.

A list of organizations represented on this committee can be obtained on request to its secretary.

### **Cross-references**

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

### **Summary of pages**

This document comprises a front cover, an inside front cover, the IEC/TS title page, pages 2 to 19 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This Draft for Development was published under the authority of the Standards Policy and Strategy Committee on 31 July 2006

© BSI 2006

ISBN 0 580 48663 X

### **Amendments issued since publication**

Amd. No.	Date	Comments

# TECHNICAL SPECIFICATION

# IEC TS 60034-17

Fourth edition  
2006-05

---

---

**Rotating electrical machines –**

**Part 17:**

**Cage induction motors when fed  
from converters – Application guide**



Reference number  
CEI/IEC/TS 60034-17:2006

## CONTENTS

INTRODUCTION.....	3
1 Scope.....	4
2 Normative references.....	4
3 Characteristics of the motor .....	4
4 Frequency spectrum of voltage and/or currents .....	5
5 Losses caused by harmonics .....	7
6 Torque derating during converter operation .....	10
7 Oscillating torques .....	11
8 Magnetically excited noise .....	12
9 Service life of the insulation system .....	13
10 Bearing currents .....	15
11 Installation (cabling, grounding, bonding) .....	18
12 Maximum safe operating speed.....	18
13 Power factor correction .....	19
Figure 1 – Waveform of phase current $i_{\text{phase}}$ in delta connection for current source converter supply (idealized example).....	5
Figure 2 – Waveform of line-to-line voltage $u_{\text{LL}}$ for voltage source converter supply with switching frequency $f_s = 30 f_1$ (example) .....	6
Figure 3 – Example for the dependence of the motor losses caused by harmonics $P_h$ , related to the losses $P_{f1}$ at operating frequency $f_1$ , on the switching frequency $f_s$ in case of voltage source converter supply .....	7
Figure 4 – Influence of converter supply on the losses of a cage induction motor (frame size 315 M, design N) with rated values of torque and speed .....	9
Figure 5 – Fundamental voltage $U_1$ as a function of operating frequency $f_1$ .....	10
Figure 6 – Torque derating factor for cage induction motors of design N, IC 0141 (self-circulating cooling) for current source converter supply as a function of operating frequency $f_1$ (example) .....	11
Figure 7 – Limiting curve of admissible impulse voltage $\hat{U}_{\text{LL}}$ (including voltage reflection and damping) at the motor terminals as a function of the rise time $t_r$ .....	14
Figure 8 – Definition of the peak rise time $t_r$ of the voltage at the motor terminals.....	14
Figure 9 – Ring flux including shaft voltage and resulting circulating current $i_{\text{circ}}$ .....	15
Figure 10 – Common mode circuit model and bearing voltage $u_{\text{brg}}$ .....	17